




LITHIUM CELLS OR BATTERIES TEST SUMMARY  
IN ACCORDANCE WITH SUB-SECTION 38.3  
OF MANUAL OF TESTS AND CRITERIA

**BATTERY TRANSPORTATION INFORMATION**

Name of cell, battery or product manufacturer, as applicable:  Rechargeable Li-ion Battery DH1210CFLP Product Manufacturer: DAP B.V.		Cell, battery or product manufacturer's contact information to include address, phone number, email address and website for more information:  Factory: Zhejiang Xindong Energy Technology Co., Ltd No.16 Hongyun Road, Lanjiang Street, Lanxi County, Jinhua City, Zhejiang Province, China 0579-88812088 E-mail: depower@depower.com.cn Website: www.depower.com.cn  Legal Manufacturer: DAP B.V. Tussendiepen 4a 9206 AD Drachten Website: www.philips.com																												
Name of the test laboratory to include address, phone number, email address and website for more information:  Shenzhen Precise Testing Technology CO., LTD Floor 1-5., Building 4-7, Tongfuyu Industrial Park, Aiqun Road, Shangwu Community, Shiyuan Street, Baoan District, Shenzhen, Guangdong, China TEL: +86-755-23406061 E-mail: precise@ptl-global.com URL: http://www.ptl-global.com		Unique test report identification number:  S-24011503A0	Date of the test report:  2024-03-06																											
Description of cell or battery to include at a minimum: Lithium ion or Lithium metal cell or battery; Mass; Watt-hour rating, or lithium content; Physical description of the cell/battery; and Model numbers:  Name: Rechargeable Li-ion Battery Type: DH1210CFLP Nominal Voltage: 14.4V Capacity/energy: 2300mAh 33.12Wh Mass: 202.51 g Appearance: Blue almost cuboid		List of tests conducted and results (i.e., pass/fail): <table border="1"><thead><tr><th>No.</th><th>Name of test</th><th>Conclusion</th></tr></thead><tbody><tr><td>1</td><td>Altitude simulation</td><td>P</td></tr><tr><td>2</td><td>Thermal test</td><td>P</td></tr><tr><td>3</td><td>Vibration</td><td>P</td></tr><tr><td>4</td><td>Shock</td><td>P</td></tr><tr><td>5</td><td>External Short-circuit</td><td>P</td></tr><tr><td>6</td><td>Impact</td><td>P</td></tr><tr><td>7</td><td>Overcharge</td><td>P</td></tr><tr><td>8</td><td>Forced discharge</td><td>P</td></tr></tbody></table>		No.	Name of test	Conclusion	1	Altitude simulation	P	2	Thermal test	P	3	Vibration	P	4	Shock	P	5	External Short-circuit	P	6	Impact	P	7	Overcharge	P	8	Forced discharge	P
No.	Name of test	Conclusion																												
1	Altitude simulation	P																												
2	Thermal test	P																												
3	Vibration	P																												
4	Shock	P																												
5	External Short-circuit	P																												
6	Impact	P																												
7	Overcharge	P																												
8	Forced discharge	P																												
Reference to assembled battery testing requirements, if applicable (i.e., 38.3.3(f) and 38.3.3(g)):  Not applicable		Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto, if any: UNITED NATIONS Manual of Tests and Criteria ST/SG/AC.10/11/Rev.7&Amend.1 38.3																												
<b>PRODUCT CLASSIFICATION FOR TRANSPORT</b>																														
UN Classification: UN3480	Proper Shipping Name: Lithium-ion batteries																													
Signature with name and title of signatory as an indication of the validity of information provided:    Suzan Vink, Quality Project Lead		This 'UN38.3 Test Summary' document remains valid as long as no changes, modifications, or additions are made to the model(s) described in this document, after being transported from a [MDBTC] facility. The model(s) has (have) been classified according to the applicable transport regulations and the UN Manual of Tests and Criteria as of the date that this document was generated. The model(s) must be packaged, labeled, and documented according to applicable regulations for transportation.																												
Date this document was generated: 18/06/2024																														