

ASUS ROG Rapture GT-AC2900



EAN:
4718017187497

Produkt Nummer:
90IG04Z0-MM2000

Highlights

- Spielbeschleuniger in drei Stufen – Optimiert deine Online-Gaming-Datenpakete auf dem gesamten Weg vom PC bis zum Game-Server.
- GeForce Now Recommended Router – Erlebe Cloud-Gaming in einer unerreichten Qualität und ohne Lags.
- AiMesh-Unterstützung – Arbeitet mit ASUS-AiMesh-kompatiblen Routern zusammen, um ein leistungsfähiges, flexibles und nahtlos verfügbares WLAN-System für das ganze Haus aufzubauen.
- Netzwerksicherheit an vorderster Front – Der kostenlose Schutz mit AiProtection Pro powered by Trend Micro gilt ein Leben lang und schützt alle angeschlossenen Geräte vor Bedrohungen aus dem Internet.
- ASUS Aura-Beleuchtung – Verschiedene Effekte für eine stylische Optik, die sogar konfiguriert werden können, um den Status deines Netzwerks anzuzeigen.

Spezifikationen

Netzwerkstandard	IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, IPv4, IPv6
Produkt-Segment	AC2900 ultimate AC performance : 750+2167 Mbps
Abdeckung	Very large homes
Datenrate	802.11a : 6,9,12,18,24,36,48,54 Mbps 802.11b : 1, 2, 5.5, 11 Mbps 802.11g : 6,9,12,18,24,36,48,54 Mbps 802.11n : up to 450 Mbps 802.11ac : up to 1733 Mbps 1024QAM (2.4GHz) : up to 750 Mbps 1024QAM (5GHz) : up to 2167 Mbps
Antenne	External detachable antenna x 3 Internal antenna x 1
Senden/Empfangen	MIMO technology 2.4 GHz 3 x 3 5 GHz 4 x 4
Prozessor	1.8 GHz 64 bit dual-core processor
Arbeitsspeicher	256 MB Flash 512 MB RAM
WLAN-Technologie	Beamforming: standard-based and universal 1024-QAM high data rate 20/40/80/160 MHz bandwidth Up to 15 DFS channels supported
Betriebsfrequenz	2.4 GHz / 5 GHz
Verschlüsselung	64-bit WEP, 128-bit WEP, WPA2-PSK, WPA-PSK, WPA-Enterprise , WPA2-Enterprise , Radius with 802.1x, WPS support
Firewall & Zugangskontrolle	Firewall?SPI intrusion detection,DoS protection Access control?Parental control, Network service filter, URL filter, Port filter
Management	UPnP, IGMP v1/v2/v3, DNS Proxy, DHCP, NTP Client, DDNS, Port Trigger, Port Forwarding, DMZ, System Event Log

VPN Support	IPSec Pass-Through PPTP Pass-Through L2TP Pass-Through PPTP server OpenVPN server PPTP client L2TP client OpenVPN client
WAN Anschluss	Internet connection type : Automatic IP, Static IP, PPPoE(MPPE supported), PPTP, L2TP
Dienstprogramme	Router setup wizard; Firmware restoration; Device discovery; printer setup utility
Anschlüsse	RJ45 for 10/100/1000/Gigabits BaseT for WAN x 1, RJ45 for 10/100/1000/Gigabits BaseT for LAN x 4 USB 2.0 x 1 USB 3.0 x 1
Features	Range Boost Router app Link Aggregation - 802.3ad MU-MIMO Airtime Fairness Smart Connect Traffic Analyzer Adaptive QoS WTFast Gamers Private Network AiProtection Pro Parental Control Guest Network : 2.4 GHz x 3, 5 GHz x 3 Mac OS Backup Enhanced media server (AiPlayer app compatible) - Image : Jpeg - Audio : mp3, wma, wav, pcm, mp4, lpcm, ogg - Video : asf, avi, divx, mpeg, mpg, ts, vob, wmv, mkv, mov AiCloud personal cloud service 3G/4G data sharing Printer Server - Multifunctional printer support (Windows only) - LPR protocol support Download Master - Support bt, nzb, http, ed2k - Support encryption, DHT, PEX and magnet link - Upload and download bandwidth control - Download scheduling AiDisk file server - Samba and FTP server with account management IPTV support Roaming Assist Bandwidth Limiter
Bedienung	WPS Button, Reset Button, Power Button, Wireless on/off Button, LED on/off Button, Boost Key
LED Anzeige	Wi-Fi x 2 WAN x 1
Stromleistung	AC Input : 110V~240V(50~60Hz) DC Output : 19 V with max. 1.75 A current
Betriebssysteme	Windows® 10 Windows® 8 Windows® 7 Mac OS X 10.6 or Above Linux
Abmessungen	221 x 169 x 111 mm (WxHxD) g
Gewicht	780 g
Lieferumfang	GT-AC2900 Wi-Fi Router Dual-purpose stand/ wall-mount Power adapter RJ-45 cable Screwdriver Quick start guide

Betriebsmodus

- Wireless router mode
- Range extender mode
- Access point mode
- Media bridge mode